


RATING AND CHARACTERISTICS

Standard Varistors - 32mm

Oridring Code 	Varistor Voltage at 1mA	Maximum Allowable Voltage		Maximum Clamping Voltage		Withstanding Surge Current (8/20us)	Energy (10/1000us)
	DC (V)	AC rms (V)	DC (V)	Vc (V)	IP (A)	1 Time (A)	(J)
JVR 32N201K□△△	200 (185~225)	130	170	340	200	20000	250
JVR 32N241K□△△	240 (216~264)	150	200	395			290
JVR 32N271K□△△	270 (243~297)	175	225	455			300
JVR 32N331K□△△	330 (297~363)	210	275	550			360
JVR 32N361K□△△	360 (324~396)	230	300	595			380
JVR 32N391K□△△	390 (351~429)	250	320	650			400
JVR 32N431K□△△	430 (387~473)	275	350	710			430
JVR 32N471K□△△	470 (423~517)	300	385	775			460
JVR 32N511K□△△	510 (459~561)	320	415	845			510
JVR 32N621K□△△	620 (558~682)	385	505	1025			570
JVR 32N681K□△△	680 (612~748)	420	560	1120			600
JVR 32N751K□△△	750 (675~825)	460	615	1240			620
JVR 32N781K□△△	780 (702~858)	485	640	1290			660
JVR 32N821K□△△	820 (738~902)	510	670	1355			700
JVR 32N911K□△△	910 (819~1001)	550	745	1500			750
JVR 32N951K□△△	950 (855~1045)	575	765	1570			780
JVR 32N102K□△△	1000 (900~1100)	625	825	1650			810
JVR 32N112K□△△	1100 (990~1210)	680	895	1815			910
JVR 32N122K□△△	1200 (1080~1320)	750	990	1980			960