

JNR25S series

Diameter	Model No.	Resistance at 25°C (Ω)	Thermal dissipation coefficient (mW/°C)	Thermal Time constant (S)	I _{max} (A)	Maximum Capacitance AC240V (uF)	Rated Temperature TL~TU(°C)
25D	25S1R0M	1.0	≥29	≤180	15.0	1200	-40~+200
	25S1R0L	1.0			15.0		
	25S1R3M	1.3			15.0		
	25S1R3L	1.3			15.0		
	25S1R5M	1.5			15.0		
	25S1R5L	1.5			15.0		
	25S2R0M	2.0			14.5		
	25S2R0L	2.0			14.5		
	25S2R5M	2.5			14.5		
	25S2R5L	2.5			14.5		
	25S030M	3.0			14.5		
	25S030L	3.0			14.5		
	25S040M	4.0			14.0		
	25S040L	4.0			14.0		
	25S4R7M	4.7			13.0		
	25S4R7L	4.7			13.0		
	25S050M	5.0			11.0		
	25S050L	5.0			11.0		
	25S6R8L	6.8			10.5		
	25S070L	7.0			10.0		
	25S080L	8.0			9.0		
25S100L	10.0	8.0					
25S120L	12.0	7.5					
25S150L	15.0	6.5					

25S180L	18.0
25S200L	20.0

5.5
5.0