

## 40X40X28 mm

## SF0428-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF0428B1TR	B	12	10.2 ~ 13.2	37.50	4.445	27000	2.45	29.4	2.70	67	52
SF0428B1UR				34.66	3.730	25000	1.58	18.96	1.80	65	
SF0428B1SR			10.2 ~ 13.8	31.24	2.980	22000	1.22	14.64	1.50	62	
SF0428B1HR				25.12	1.930	18000	0.64	7.68	0.80	57.5	
SF0428B1MR				19.82	1.260	15000	0.44	5.28	0.60	53.5	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

